

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 240 916 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
18.09.2002 Bulletin 2002/38

(51) Int Cl.7: **A61M 37/00**, **A61M 5/178**,
A61M 5/00

(21) Application number: **02005279.1**

(22) Date of filing: **11.03.2002**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Nakajima, Hiroaki, Medikit Co., Ltd.**
Tokyo (JP)

(74) Representative: **Moutard, Pascal Jean et al**
Cabinet Beau de Loménie,
Postfach 15 04 27
80043 München (DE)


(30) Priority: **12.03.2001 JP 2001068570**

(71) Applicant: **Medikit Co., Ltd.**
Tokyo, 113-0034 (JP)

(54) Valve structure of indwelling catheter

(57) An indwelling catheter has a hollow catheter body, a catheter tube fitted to a front end of the catheter body, an elastic valve fitted inside the catheter body, and a hollow plug slidably fitted inside the catheter body. The

catheter tube, the elastic valve, and the plug are aligned in this order. A connector inserted from a proximal end of the catheter pushes the plug, and the plug presses the elastic valve open.

FIG. 1**EP 1 240 916 A1**

EP 1 240 916 A1

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This invention relates to an indwelling catheter for use in artificial dialysis, fluid infusion, or blood infusion, and more particularly, to an indwelling catheter which avoids backflow of blood outside the catheter when the needle is inserted/removed and allows a connector to be connected thereto with very small force, reducing load to a patient.

2. Description of the Related Art

[0002] United States Patent No. 5,911,710 discloses an art related to an indwelling catheter. The indwelling catheter disclosed is a medical insertion device for introducing an elongated tube into a blood vessel and manipulating the tube while maintaining hemostasis. The indwelling catheter has a sheath housing and a shuttle housing. A sheath valve is fitted inside the sheath housing. A shuttle tube is provided in the shuttle housing. When the shuttle housing is pushed forward, the shuttle tube makes the sheath valve open. The use of this indwelling catheter allows tube manipulation while maintaining hemostasis.

SUMMARY OF THE INVENTION

[0003] The above indwelling catheter has a hemostatic valve provided in the vicinity of an insertion opening of the shuttle housing for securely maintaining hemostasis in the shuttle housing. When a tube for a drip injection or the like is connected thereto, secured hemostasis is required between the tube and the shuttle housing using the hemostatic valve prior to commencing the opening operation of the sheath valve. The operation of inserting the tube into the hemostatic valve induces a great resistance force, causing the patient much discomfort. The series of operations are complicated, inviting operational errors.

[0004] This invention was made to solve the above problems, and has an object of providing an indwelling catheter with good maneuverability, securely maintaining hemostasis in a catheter body with an easy operation.

[0005] An indwelling catheter according to a first aspect of this invention comprises: a hollow catheter body; a catheter tube fitted to a front end of the catheter body; an elastic valve fitted inside the catheter body; and a hollow plug slidably fitted inside the catheter body. The catheter tube, the elastic valve, and the plug are coaxially aligned in this order. A connector inserted from a proximal end of the catheter, pushes the plug, and the plug presses the elastic valve open.

[0006] To introduce the indwelling catheter of this in-

vention into the body of a patient, a needle is inserted from a proximal end of the catheter body to protrude the tip of the needle out from a front end of the catheter tube. The needle presses the elastic valve open, closely contacting with the valve, thereby securely providing hemostasis. The removal of the needle makes the elastic valve close, so that hemostasis is maintained until a drip tube or the like is connected. The connector for connecting a drip tube or the like, when inserted from the proximal end of the catheter body, presses the rear end of the plug with its front end, sliding the plug forward. Then the front end of the plug presses the elastic valve open, maintaining hemostasis and easily providing connection between the drip tube or the like and the indwelling catheter.

[0007] An indwelling catheter according to a second aspect of this invention has a biasing means for biasing the plug in a direction opposite to the elastic valve. The biasing means comprises a coil spring or a bellows.

[0008] In the indwelling catheter according to the second aspect, the removal of the connector makes the plug return to its original position by the biasing means, making the elastic valve automatically close, and thereby providing hemostasis. Thus the exchange of a drip tube or the like does not require a special operation for hemostasis. This facilitates the exchange of a drip tube or the like.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009]

FIG. 1 is a longitudinal cross-sectional view of an indwelling catheter according to a first embodiment of this invention, being ready for insertion into the body of a patient;

FIG. 2 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 1 with a needle removed; FIG. 3 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 2 with a connector connected thereto;

FIG. 4 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 3 with the connector removed;

FIG. 5 is a longitudinal cross-sectional view of an indwelling catheter according to a second embodiment of this invention, being ready for insertion into the body of a patient;

FIG. 6 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 5 with a needle removed; FIG. 7 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 6 with a connector connected thereto;

FIG. 8 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 7 with the connector removed;

FIG. 9 is a longitudinal cross-sectional view of an indwelling catheter according to a third embodiment

EP 1 240 916 A1

of this invention, being ready for insertion into the body of a patient;

FIG. 10 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 9 with a needle removed;

FIG. 11 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 10 with a connector connected thereto; and

FIG. 12 is a longitudinal cross-sectional view of the indwelling catheter of FIG. 11 with the connector removed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0010] With reference to FIGS. 1 to 4, a first embodiment of this invention will be described in detail below.

[0011] An indwelling catheter A according to the first embodiment of this invention has, as shown in FIG. 1, a hollow catheter body 1, a catheter tube 2 fitted into a tube holder 1b provided at a distal end of the catheter body 1, an elastic valve 3 fitted inside the catheter body 1, and a hollow plug 4 slidably fitted inside the catheter body 1. The catheter tube 2, the elastic valve 3, and the plug 4 are coaxially aligned in this order.

[0012] The catheter body 1 is made from resin or a like material, and has a tubular shape. An inner surface 1a is tapered toward the distal end, with a gradually reduced diameter.

[0013] The catheter body 1 is preferably of a transparent or semi-transparent material so as to show the interior, enabling checking of movement inside.

[0014] The catheter tube 2 is made from resin such as polyamide, and is press-fitted into the tube holder 1b which communicates at its proximal end with the inside of the catheter body 1.

[0015] It is preferred that a lubricating coating is provided to the entirety or part of the catheter tube 2 so as to reduce resistance caused by insertion through skin or into a blood vessel.

[0016] The elastic valve 3 is of a generally tubular shape, having a closed front surface. The front surface centrally has an openable/closable valve aperture 3a. At an inner surface of a rear opening of the valve 3, an annular protrusion 3b to engage the plug 4 is provided.

[0017] The valve aperture 3a is closed watertight when the plug 4 and the needle 5 are not inserted therethrough, providing hemostasis. With the plug 4 inserted therethrough, the valve aperture 3a expands forward and opens, providing communication between the catheter tube 2 and the rear of the catheter body 1.

[0018] The annular protrusion 3b protrudes inwardly so as to slidably contact with an outer periphery of the plug 4. The protrusion 3b engages a shoulder 4c provided at a distal end of the plug 4 so as to slidably prevent the dislocation of the plug 4.

[0019] A plurality of gaps 3c is defined between an outer periphery of the elastic valve 3 and the inner surface 1a of the catheter body 1. Distal and proximal spaces

divided by the elastic valve 3 communicate with each other through the gaps 3c. Thus the elastic valve 3 slides smoothly with air passing through the gaps 3c.

[0020] The plug 4 is made from resin or a like material, and has an inner passageway. The plug 4 has a tubular portion 4a, a conical flange 4b connected to the rear end of the tubular portion 4a, and the shoulder 4c protruding from an outer periphery of the tubular portion 4a.

[0021] A front end of the tubular portion 4a is chamfered to facilitate its penetration into the valve aperture 3a of the elastic valve 3, and is slidably supported by the annular protrusion 3b of the elastic valve 3.

[0022] The conical flange 4b has a conical inner surface so as to facilitate insertion of the needle 5 thereinto. The peripheral surface of the flange 4b contacts the inner surface 1a of the catheter body 1 and serves to provide stability to the plug 4 and maintain the coaxial position with respect to the catheter tube 2.

[0023] The indwelling catheter A of this embodiment is prepared for use in such a state as shown in FIG. 1 with the front end of the needle 5 protruding from the front end of the catheter tube 2. In this state, the needle 5 penetrates through the elastic valve 3, providing water-tight connection therebetween, and thereby preventing leakage of blood.

[0024] The indwelling catheter A in this state is inserted into the body of a patient. Then, as shown in FIG. 2, the needle 5 is removed with the tube 2 retained in the body of the patient. The elastic valve 3, being retained in position by an annular protrusion 1e, still remains in the catheter body 1 when the needle 5 is removed, being closed to maintain hemostasis.

[0025] Then, the connector 6 is inserted from the rear end of the catheter body 1. When pressed into the catheter body 1, the connector 6 pushes at its front end the plug 4. The plug 4 thus slides forward to press at its front end the valve aperture 3a of the elastic valve 3 open. The elastic valve 3 is then pressed against the inner surface of a tapered cavity 1c of the catheter body 1 as shown in FIG. 3, and stops its movement, thus providing communication between the catheter tube 2 and a tube for a drip or the like. The tapered inner surface 1a of the catheter body 1 allows for smooth insertion of the connector 6 and tight contact between an outer surface 6a of the connector 6 and the inner surface 1a through press fitting. The plug 4 is brought into close contact with the elastic valve 3, and the outer surface 6a of the connector 6 is brought into close contact with the inner surface 1a of the catheter body 1, securely providing hemostasis.

[0026] With reference to FIGS. 5 to 8, a second embodiment of this invention will be described. In these figures, elements substantially identical with those in the first embodiment are referred to with the same reference numerals. Different or new elements are referred to with new reference numerals.

[0027] An indwelling catheter B according to the second embodiment has the structure identical to that of the

5

EP 1 240 916 A1

6

indwelling catheter A, and further includes a coil spring 7 biasing a plug 4 in a direction opposite to an elastic valve 3. The coil spring 7 is made from a resilient material and is fitted between the elastic valve 3 and the plug 4.

[0028] A connector 6 is inserted from the rear of a catheter body 1 to press the plug 4 against the biasing force of the coil spring 7. The front end of the plug 4 then penetrates into a valve aperture 3a of the elastic valve 3, providing connection between a catheter tube 2 and a drip tube or the like as shown in FIG. 7.

[0029] Then, the connector 6 is removed, and the plug 4 is returned to its original position by the biasing force of the coil spring 7 as shown in FIG. 8. The elastic valve 3 is thus closed, providing hemostasis. That is, the removal of the connector 6 does not require a special operation for hemostasis, resulting in hemostasis being reliably maintained.

[0030] With reference to FIGS. 9 to 12, a third embodiment of this invention will be described. In these figures, elements substantially identical with those in the first embodiment are referred to with the same reference numerals. Different or new elements are referred to with new reference numerals.

[0031] An indwelling catheter C according to the third embodiment has the structure identical to that of the indwelling catheter B, and has a bellows 8 in place of the coil spring 7 for biasing a plug 4 in a direction opposite to an elastic valve 3. The bellows 8 is made from a resilient material and is fitted between the elastic valve 3 and the plug 4.

[0032] A connector 6 is inserted from the rear of a catheter body 1 to press the plug 4 against the biasing force of the bellows 8. The front end of the plug 4 then penetrates into a valve aperture 3a of the elastic valve 3, providing connection between a catheter tube 2 and a drip tube or the like as shown in FIG. 11.

[0033] Then the connector 6 is removed, and the plug 4 is returned to its original position by the biasing force of the bellows 8 as shown in FIG. 12. The elastic valve 3 is thus closed, providing hemostasis. That is, the removal of the connector 6 does not require a special operation for hemostasis, resulting in hemostasis being securely maintained.

[0034] The preferred embodiments of this invention described above are not meant to be limiting. A person with ordinary skill in the art may change or modify the embodiments to implement this invention, based on the above disclosure.

Claims

1. An indwelling catheter, comprising:

a hollow catheter body (1);
a catheter tube (2) fitted to a front end of the catheter body (1);

an elastic valve (3) fitted inside the catheter body (1); and
a hollow plug (4) slidably fitted inside the catheter body (1); wherein,
the catheter tube (2), the elastic valve (3), and the plug (4) are aligned in this order; and
a connector inserted from a proximal end of the catheter body (1) pushes the plug (4), and the plug (4) presses the elastic valve (3) open.

2. An indwelling catheter as set forth in claim 1, wherein the catheter body (1) has an inner surface (1a) in a tapered shape.
3. An indwelling catheter as set forth in claim 1 or 2, wherein one or more gaps (3c) are provided between the elastic valve (3) and the catheter body (1), to provide an air passage.
4. An indwelling catheter as set forth in claim 1 to 3, wherein the plug (4) is slidably prevented from slipping out from inside the catheter body (1).
5. An indwelling catheter as set forth in claim 1 to 4, wherein the plug (4) is slidably fitted to the elastic valve (3).
6. An indwelling catheter as set forth in claim 1 to 5, wherein the elastic valve (3) has an annular protrusion (3b), and the plug (4) has a shoulder (4c) slidably engaging the annular protrusion (3b), the plug (4) being prevented from slipping out from the elastic valve (3).
7. An indwelling catheter as set forth in claim 1 to 6, further comprising a biasing means fitted outside the plug, the biasing means biasing the plug (4) in a direction opposite to the elastic valve (3).
8. An indwelling catheter as set forth in claim 7, wherein the biasing means comprises a bellows (8) or a spring coil (7) made of a resilient material.

50

55

4

EP 1 240 916 A1

FIG.1




FIG.2





FIG.3



EP 1 240 916 A1

FIG.4




FIG.5





FIG.6



EP 1 240 916 A1

FIG.7




FIG.8





FIG.9



EP 1 240 916 A1

FIG.10




FIG.11





FIG.12



EP 1 240 916 A1

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 00 5279

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 599 305 A (FREISLINGER KIRSTEN ET AL) 4 February 1997 (1997-02-04) * the whole document *	1-8	A61M37/00 A61M5/178 A61M5/00
A	US 5 350 363 A (GOODE ROBERTA D ET AL) 27 September 1994 (1994-09-27) * the whole document *	1-8	
A	US 5 458 640 A (GERRONE CARMEN J) 17 October 1995 (1995-10-17) * the whole document *	1-8	
A	US 5 584 808 A (HEALY PATRICK M) 17 December 1996 (1996-12-17) * the whole document *	1-7	
D,A	US 5 911 710 A (LAMBRECHT GREGORY ET AL) 15 June 1999 (1999-06-15) * the whole document *	1-8	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A61M
Place of search MUNICH		Date of completion of the search 11 June 2002	Examiner De Meyere, P
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document Y : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EP 1 240 916 A1

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 00 5279

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-06-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5599305	A	04-02-1997	DE 69522528 D1	11-10-2001
			DE 69522528 T2	02-05-2002
			EP 1108442 A2	20-06-2001
			EP 0709108 A2	01-05-1996
			JP 8206218 A	13-08-1996
			US 2002058910 A1	16-05-2002
			US 6338725 B1	15-01-2002
			US 5843031 A	01-12-1998
US 5350363	A	27-09-1994	US 5538505 A	23-07-1996
US 5458640	A	17-10-1995	US 5312351 A	17-05-1994
			US 5320508 A	14-06-1994
US 5584808	A	17-12-1996	NONE	
US 5911710	A	15-06-1999	AT 211402 T	15-01-2002
			AU 6378198 A	05-11-1998
			CA 2236608 A1	02-11-1998
			DE 69803329 D1	28-02-2002
			EP 0875262 A2	04-11-1998
			JP 11004894 A	12-01-1999

EP 02 00 5279

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.